

METAL FINDING

MetalliScanner® MT 6



Locate embedded metal before your drill bit or saw blade does. This powerful dedicated metal scanning tool can locate metal up to 6 inches deep in solid concrete.

MetalliScanner® MT 6 locates both ferrous and non-ferrous metal up to 6 inches (152 mm) deep in concrete and other non-metallic surfaces. It also differentiates between ferrous and non-ferrous metal targets and indicates the target depth in inches and centimeters.

MT 6 indicates when you are approaching a metal object with a large plus (+) sign on the display. When the plus becomes a minus (-), you have crossed over the target and are now moving away.

Use MetalliScanner® MT 6 to find or avoid rebar, cables, pipe, nails in reclaimed wood, nails/tacks in studs behind lath & plaster walls, electrical boxes and conduit, and more.

MetalliScanner® MT 6 is the tool recommended by the My Safe Florida Home Program to assist in hurricane loss mitigation.

- Automatically differentiates between magnetic metal (such as rebar) and non-magnetic metal (such as copper pipe)
- Shows the depth of metal from the surface in both inches and centimeters
- Easy-to-read LCD screen pinpoints the location of metal objects to the nearest ½ inch (13 mm) and depth to the nearest inch (25 mm)
- Helps map out the grid of metal through any nonmetallic construction material, including concrete, tile, and marble



Scan for Metal



SPECIFICATIONS

| | |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| Dimensions | 8.94 in. H x 3.84 in. W x 2.23 in. D (227 mm x 98 mm x 57 mm) |
| Weight | 9.17 oz. (260 g) without battery |
| Battery Type | 9V alkaline (not included) |
| Position Accuracy | Center of #4 (½ in.) rebar or ½ in. (13 mm) copper pipe at a minimum grid spacing of 6 in. (152 mm) typically within ½ in. (13 mm) |
| Depth* | Up to 6 in. (152 mm) ± 1 in. (25 mm) |
| Operating Temperature | 20° to 105°F (-7° to 41°C) |
| Storage Temperature | -20° to 150°F (-29° to 66°C) |
| Humidity | 5-90% RH non-condensing |
| Water Resistance | Splash and water resistant, not waterproof |

*NOTE: See tool's instructions for more information. Sensing depth and accuracy can vary due to moisture, content of materials, wall texture, paint, etc.